PAGE 5/8 \* RCVD AT 4/14/2004 3:37:42 PM [Eastern Daylight Time] \* SVR:USPTO-EFXRF-1/9 \* DNIS:8729306 \* CSID:2122442233 \* DURATION (mm-55):02-10

Docket No.: SCHMITT-13 Appl. No.: 10/047,486

AMENDMENTS TO THE CLAIMS WITH MARKINGS TO SHOW CHANGES

MADE, AND LISTING OF ALL CLAIMS WITH PROPER INDENTIFIERS

1. (Canceled)

2. (Currently amended) The method of claim [[1]] 4, wherein the opposite side

edges are beveled towards one side so as to form an inner side and an outer

side, with the inner side having a surface area which is smaller than a surface

area of the outer side.

3. (Currently amended) The method of claim [[1]] 4, wherein the bending step

and the shaping step are implemented by a roll forming operation.

4. (Currently amended) [[The]] A method of claim 1 of securing a rod-shaped

part in a surrounding holding member, comprising the following steps:

fabricating a flat holding member having opposite side edges formed with

elements configured for interlocking engagement;

bending the side edges of the holding member upwards:

shaping the holding member into a cross-section in accordance to a cross

section of the rod-shaped part;

inserting the rod-shaped part into the holding member; and

press-fitting the holding member about the rod-shaped part to permanently

connect the holding member to the rod-shaped part, wherein the press-fitting

step includes a first pressing operation at one position of the holding memb r

PAGE 6/8 \* RCVD AT 4/14/2004 3:37:42 PM [Eastern Daylight Time] \* SVR:USPTO-EFXRF-1/9 \* DNIS:8729306 \* CSID:7122442233 \* DURATION (mm-55):02-10

Docket No.: SCHMITT-13 Appl. No.: 10/047,486

so that the holding member assumes a non-round configuration, and at least

two a second pressing operations operation which act-on-the holding-member

at a positions position offset to the one another position by 90° to conform to

the cross section of the rod-shaped part.

5. (Currently amended) The method of claim [[1]] 4, wherein the rod-shaped

part has a radial profile.

6. (Original) The method of claim 5, wherein the rod-shaped part has a thread.

7. (Original) The method of claim 6, wherein the rod-shaped part is a threaded

гоd.

8. (Currently amended) The method of claim [[1]] 4, wherein the rod-shaped

part has a circular cross section.

Claims 9-17 (Canceled)